

CONNECTING & INSULATION ELEMENTS SPECIAL CLAMP FOR CARFLEX SUPER AND MASTER-PUR

Car-Grip Hose Clamp, Screwable

Material

- Clamp band: 201 stainless steel
- Screw casing: 201 stainless steel
- Bridge: 201 stainless steel

Applications

- Special clamp for securing Carflex Super, Master-PUR STEP, Master-PUR SL, L, H, L-X & H-X.

Properties

- Rust-resistant
- Easy to install
- Robust
- Primarily tight and tear-proof connection via bridge profiles

Construction

- Hose clamp with one or more worm-gear drive
- Hexagon head screw
- One or more spot-welded bridges

Standard Production

- Diameter: 2.4" to 16"

Available on Request

- Other clamping ranges
- Reinforced clamps with additional bridges

Torque

- Maximum recommended installation of torque is 42 lb.-in. (4.7 Nm)

Note: damage may occur to the clamp or connector if tightened above maximum recommendation.



Master-Clip Hose Dia (in.)	Clamping Range (in.)	Product Code
2.4" to 16"	2.4" to 16"	531-060-100 to 531-250-100

We recommend our standard clamp with worm-gear drive or our heavy-duty clamp with bolts for securing other spiral hoses.