

# EXHAUST GAS HOSE FOR TEMPERATURES UP TO +350°F

## Carflex 350

### Material

Hose wall: neoprene-coated polyester fabric  
External helix: galvanized steel with additional plastic abrasion protector

### Applications

- Medium duty exhaust gas extraction from gas or diesel engines
- All normal exhaust extraction systems, such as, hose reel, slotted channels, above-floor and under-floor, suction extraction


### Properties

- Flame-resistant to UL94 criteria
- Vibration-proof
- Good flow characteristics
- Extremely flexible
- Compressibility 1:5
- Small bend radius
- Super lightweight
- Extra strength
- Special clamping method guarantees high tensile strength between hose material and external helix
- To maximize life of duct and exhaust system effectiveness, it is recommended to utilize a negative pressure exhaust system and introduce ambient air at the inlet.



### Construction

1. External helix
2. Additional abrasion protector
3. Hose wall: neoprene-coated polyester fabric



### Temperature Range

- Exhaust gas temperatures up to +350°F when exhaust gas funnels are used properly and enough fresh air is utilized

### Chem. Resistance

See resistance table

# Carflex 350

Dia (in.)	Outer Dia (in.)	Negative (in. w.c.)	*Bending radius (in.)	Weight (lbs./ft.)	Product Code
4.00	4.68	40	2.40	0.53009	240-100-118
5.00	5.68	26	3.00	0.63745	240-125-118
6.00	6.68	18	3.60	0.98637	240-150-118
8.00	8.68	10	4.80	1.18096	240-200-118

\*Referring to the inner side of the elbow of hose.

The above mentioned data refers to an average and ambient temperature of 68° F. Subject to technical changes and color variations. Please refer to technical data sheet when selecting hose.

## Installation and connection possibilities



Clip-Grip hose clamp, screwable



Hose connector



Hose reducer, symmetrical

## Standard Production

- Diameter: 4" to 8"
- Color: black, outer abrasion protector blue
- Standard lengths: 25'

## Available on Request

- Special lengths
- Fix lengths with mounted Clip-Grip-clamps
- Abrasion protection profile in other colors
- Custom design with other pitches and helix sizes
- Special diameters metric

Masterduct, Inc.  
5235 Ted Street  
Houston, TX 77040  
USA  
Tel. +1.713.462.5779  
Tel. +1.800.318.3300  
Fax +1.713.939.8441  
www.masterduct.com

 **MASTERDUCT**  
Connecting Values

070715 item\_21 Car Flex 350